



Considerations for RTCA Phase 2 Low Size, Weight, and Power (SWAP) Surveillance Requirements

Presented to RTCA SC-228 Working Group 1






Foreword

- This briefing consists of suggested issues and problems when integrating low size, weight, and power surveillance systems onto UAS for the purposes of detect and avoid.
- Main purpose is to exchange information and get feedback.
- Desired feedback
 - What to add?
 - What to edit?
 - What to delete?
- These issues/problems become ours (working group 1).
 - Not just mine or NASA's



Outline

- Background
- Scope of this Topic White Paper
 - What Needs to be Addressed on this Topic in the Phase II MOPS?
 - What Does Not Need to be Addressed?
- Operational Environment as it Relates to Phase II and this Topic?
- Assumptions
 - Operational Assumptions
 - Technical Assumptions
- What is the Approach to Developing this Topic in the Phase II MOPS?




Background

- Most UAS platforms can't meet the Phase 1 radar requirements due to limited size, weight, and/or power (SWAP)
 - Non-cooperative sensor for smaller class of UAS, i.e. low SWAP
 - Need to update the Phase 1 DAA MOPS to incorporate the new technologies enabled by the Phase 2 MOPS for non-cooperative surveillance
- This briefing is focused on low SWAP sensor work that will lead to development of MOPS for non-cooperative sensors



What Needs to be Addressed on this Topic in the Phase II MOPS?

- Define what low SWAP means:
 - Relative to the SWAP of the Phase 1 radar system
 - Relative to conventional cooperative surveillance system (ADS-B/Transponder)
 - Upper thresholds for volume, weight, power
- High-level objective
 - Evaluate the interoperability between the performance requirements of low SWAP surveillance with DAA alerting and guidance requirements
 - Determine how to incorporate these new technologies into DAA
 - Determine if they are sufficient




What Needs to be Addressed on this Topic in the Phase II MOPS? (cont.)

- Decide Approach:
 - Top-down solution: how far can the sensor detect intruder and declare a track, and how it stacks up with issues below

Or

- Bottom-up solution: evaluate/tune issues below that then informs detection/declaration range requirements
- Performance requirements such as
 - Detection/declaration range
 - Field of view – elevation/azimuth
 - Max number of tracked targets
 - Update rates
 - Track report fields (track ID, range, range rate, etc.)
 - Accuracy/uncertainties
 - Special cases



What Needs to be Addressed on this Topic in the Phase II MOPS? (cont.)


- Performance requirements such as
 - **Detection/declaration range**
 - Field of view – elevation/azimuth
 - Max number of tracked targets
 - Update rates
 - Accuracy/uncertainties
 - Special cases



Factors with Detection/Declaration Range

Issues:


- Maneuver performance and closure speeds (Keith covered)
- New (reduced) DAA well clear parameter (Tod covering next)
 - Appropriately scaling of DAA well clear definition (DMOD and mod tau)
- Total Pilot Response Time
 - Alert times
 - ATC coordination
 - Pilot response time
- Command latencies
- Time to establish track
- Other factors
 - Impact of weather conditions




Factors with Detection/Declaration Range

Issues:

- ***Maneuver performance and closure speeds (Keith covered)***
- ***New (reduced) DAA well clear parameter (Tod covering next)***
 - ***Appropriately scaling of DAA well clear definition (DMOD and mod tau)***
- Total Pilot Response Time
 - Alert times
 - ATC coordination
 - Pilot response time
- Command latencies
- Time to establish track
- Other factors
 - Impact of weather conditions




DAA Timeline





Total Pilot Response Time

- Pilot response time
 - Display work to shorten response time?
 - Pilot-on-the-loop?
 - Auto-executed maneuver?
 - To enable low SWAP sensor it may require us taking a look at HMI and reduce response times
- ATC coordination
 - Depending on what we determine as the SWAP thresholds, declaration ranges may not allow for DAA Corrective alerts
 - Evaluate how often there wasn't enough time for ATC coordination given an encounter with a non-cooperative intruder
 - Likely (hopefully) very, very low? Validate with fast-time study.
- Alert times
 - Parameters for DAA alerting requirements such as late alerts, early alert, minimum average alert time likely need updating
 - Can they be reduced to require less SWAP?




Communication Latencies

- Modeling Time Lags
 - Downlinking surveillance data from aircraft
 - Upload of commanded maneuver to aircraft responding
- Assumption is that this is already informed by the C2 MOPS
- Probably just need a simple model for this our our simulations




Time to Establish Track

- Time between detection of target and declaring a track
- Assumption is sensor MOPS will have requirements on this, and we will need to evaluate interoperability with DAA alerting and guidance
- Likely to just need a simple model for this in fast-time simulations




Other Factors for Detection

- Environmental conditions
 - Rain
 - Snow
 - Dust
- *Decide whether to include these, and if so how?*



What Needs to be Addressed on this Topic in the Phase II MOPS? (cont.)

- Performance requirements such as
 - Detection/declaration range
 - **Field of view – elevation/azimuth**
 - Max number of tracked targets
 - Update rates
 - Accuracy/uncertainties
 - Special cases




Azimuth/elevation

- Study the trade space to understand the encounter geometries characteristics and whether there is enough coverage to provide DAA alerts and guidance that help the pilot remain DWC (non-cooperative sensor)
- How wider field of view translates to helping the pilot remain DWC. What's the minimum?
- Some type of trade against encounter geometries and sensor field of view that show impact on DWC (non-cooperative)




What Needs to be Addressed on this Topic in the Phase II MOPS? (cont.)

- Performance requirements such as
 - Detection/declaration range
 - Field of view – elevation/azimuth
 - **Max number of tracked targets**
 - Update rates
 - Accuracy/uncertainties
 - Special cases



Max number of tracked targets

- Verify the interoperability between the maximum number of intruders tracked interoperates with DAA alerting and guidance and integrate into the airspace
 - How many tracked targets are required for suitable performance?
- Determine whether the number of tracked intruders the sensor can maintain at various update rates is sufficient/required




What Needs to be Addressed on this Topic in the Phase II MOPS? (cont.)

- Performance requirements such as
 - Detection/declaration range
 - Field of view – elevation/azimuth
 - Max number of tracked targets
 - **Update rates**
 - Accuracy/uncertainties
 - Special cases




Update rates

- Verify the interoperability between updates rates if different than 1Hz and DAA alerting and guidance requirements.
 - Maybe requirements can be traded off to accommodate the low SWAP surveillance, but still maintain acceptable safety and efficiency
 - Is it more desirable to have a large FOV that is updated less frequently (> 1 Hz), or a smaller FOV that is ≤ 1 Hz?
- Prioritization and lower update rates for lower priorities
 - Tradeoffs in DAA alerting and guidance performance



What Needs to be Addressed on this Topic in the Phase II MOPS? (cont.)

- Performance requirements such as
 - Detection/declaration range
 - Field of view – elevation/azimuth
 - Max number of tracked targets
 - Update rates
 - **Accuracy/uncertainties**
 - Special cases




Accuracy/uncertainties

- Develop requirements for interoperability with DAA alerting and guidance (hazard and non-hazard zones)
- Develop new set of accuracy requirements and test vectors
 - Determine acceptable error bounds on sensor track output
 - Incorrect alerts and missed alerts
- Get early start on passing test vectors when degraded tracks are used
 - Identify degraded tracks as soon as possible
 - Start working on surveillance uncertainty mitigations early




What Needs to be Addressed on this Topic in the Phase II MOPS? (cont.)

- Performance requirements such as
 - Detection/declaration range
 - Field of view – elevation/azimuth
 - Max number of tracked targets
 - Update rates
 - Accuracy/uncertainties
 - **Special cases**




Alerting and Guidance Special Cases

- Develop new special cases that addresses DAA interoperability challenges
 - Non-cooperative and cooperative sensors
- For example, in Phase 1, when the altitude state estimation error exceeds a threshold, there are requirements that changed how alerts are scored, i.e. alert using only horz. closure rate and horizontal miss distance estimates (not altitude)
- Airspace integration
 - Increased traffic densities will reduce total airspace volume, thus elevation capability may be more critical than in Phase 2 compared to Phase 1.



What Does Not Need to be Addressed?

- Detection of other hazards such as birds, structures, power lines, etc.
- Any feedback? What else should be added?




Operational Environment as it Relates to Phase II and this Topic?

- Assumption is operational environment is similar across all the individual white papers
 - Common operational environment for Phase 2
 - Maybe it's a little different for GBSAA compared to airborne surveillance issues cited here
- *Hope to be informed by Paul Campbell's Operational Environment briefing/white paper*




Operational Assumptions

- UAS are operating under IFR.
- Two way communication with ATC (nominal conditions following flight plan/mission)
 - However, for DAA the low SWAP timeline may not allow for mandatory ATC coordination
- Detection of non-cooperative intruders are primarily used for operation below 10,000 feet




Technical Assumptions

- Focus in this white paper/briefing is on airborne equipment
 - GBSAA will be covered by another briefing/white paper
- Surveillance system used to detect other aircraft



What is the Approach to Developing this Topic in the Phase II MOPS?

- Coordination by sensor manufacturer and DAA research organizations needs to occur
- We need encounter sets/model and traffic density values to drive testing
- Need (relatively smaller) UAS performance model (turn, climb, descent, stop/slow down) for those intending to leverage low SWAP requirements
- Need models of sensors/surveillance systems
- NAS-wide simulations will help evaluate airspace integration issues and rates of encounters/alerts for input into verifying requirements and safety risk management assessment



What is the Approach to Developing this Topic in the Phase II MOPS? (cont.)

- Human-in-the-loop simulations to verify that when low SWAP sensor requirements are integrated with DAA alerting and guidance we get acceptable pilot performance, as baselined in Phase 1 for the Phase 1 system.
- Flight test(s) to verify results collected in simulation, demonstrate the maturity of the technology integration, and validate the MOPS.



Questions???

confesor.santiago@nasa.gov